

Pré-Amplifier Range PR 100



Rating: Not Rated Yet

[Ask a question about this product](#)

Description

Possible to be directly supplied at 5V by the DVB-T receiver
 Amplifiers with low noise

REF.	PR-100	PR-101
ENTRADAS ENTRÉES ENTRADAS	1 BIII/UHF	1 UHF
BANDA COBERTA BANDE COUVERTE BAND RANGE BANDA CUBIERTA	MHz 170-860	470-860
GANHO GAIN GANANCIA		15
NÍVEL MÁXIMO SAÍDA NIVEAU MAXIMUM SORTIE MAXIMUM OUTPUT LEVEL NIVEL MÁXIMO SAÍDA		96* 93**
FACTOR DE RUIDO FACTEUR DE BRUIT NOISE FIGURE FACTOR RUIDO		<2
CONSUMO CONSUMMATION CONSUMICTION CONSUMIACION		10
ALIMENTAÇÃO ALIMENTATION SUPPLY ALIMENTACION		5...24V ---
CONEXÃO CONNECTEURS CONNECTION CONEXION		Fichas tipo "F" Fiches type "F" "F" Connectors Conectores tipo "F"

PR-101

*DIN 45004B, IMD3-60dB, 3P
 **EN 50083-3, IMD3-60dB, 2P